



## Ezi-TileFix Adhesive Product Sheet

Ezi-TileFix adhesive is the **Ezi** way to fix hollow floor & wall tiles **internally** or **externally** without the need to remove or replace the tiles and without damaging any of the surrounding tiles in **3 Ezi** steps...

### Repair kit Contents

- 1 bottle of Ezi-TileFix adhesive
- 1 adhesive applicator bottle
- 100mm plastic tubing
- 1 nozzle
- 2mm drill bit



0.5 ltr of **Ezi-TileFix** adhesive should fix approx 2-3 m2 of hollow tiles. Depending on the severity of the problem more or less **Ezi-TileFix** adhesive may be needed?

### Instructions For Use

#### Step 1

Clean the affected tile and the grout around the tile and the surrounding tiles then very carefully drill a hole in the grout in the middle of a tile joint with the supplied **2mm** drill bit to the depth or bottom of the affected tile, avoid damaging the edges of the tiles. Depending upon the size of the repair a hole in each joint around the tile may be needed.

#### Step 2

Next use a brush to carefully collect the grout dust and put it somewhere safe, or if you have some grout to match the existing grout you can use a vacuum to clean up the grout dust, then half fill the supplied **applicator** bottle with **Ezi-TileFix** adhesive being careful not to spill any.

Then place the applicator tube **nozzle** into one of the holes you have drilled in the grout and gently squeeze the applicator allowing the adhesive to flow under the tile, remove the nozzle and check that the adhesive is flowing under the tile and repeat until the space below the tile is filled completely.

Depending upon the severity of the problem you may have to repeat this step a few times in order to ensure the adhesive has flowed under the tile and completely filled the space below the tile. If the adhesive will not flow under the affected tile try one of the other holes around the affected tile, if the problem persists then repeat **step 1** and carefully drill a new set of holes in the grout.

Then clean any excess adhesive around the holes in the grout around the affected tile with a damp sponge and pour any remaining adhesive back into the **Ezi-TileFix** bottle and then store in a cool dry place (avoid freezing) out of the reach of children. *Please note* that we cannot accept responsibility for any damage caused by excess adhesive not being cleaned off the affected tile surface properly after usage.

After use flush out the applicator bottle, tube and nozzle with clean water ready for reuse.

#### Step 3

After 24 hours check there are no hollow spots under the tile, if any hollow spots are found repeat **step 2**

If no hollow spots are found mix some grout to match the existing grout and repair the holes in the grout, or mix a small amount of **Ezi-TileFix** with the grout dust you saved in **step 1** and form a paste to repair the holes in the grout around the repaired tile.

Please note that this information is provided in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. Customers are advised that product, techniques and codes of practice are under constant review and changes may occur without notice.